

Material Safety Data Sheet

PC-PLUMBING

MSDS No. 90831-53

Date of Preparation: 8-31-2009

Revision: 07

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: PC PLUMBING EPOXY PUTTY

Chemical Formula: Mixture

CAS Number: Mixture

General Use: Adhesive

Manufacturer: Protective Coating Company, 221 S. Third St., Allentown, PA 18102-4922, Phone (610)432-3543, FAX (610)432-5043 (9AM-5PM EST).

Section 2 - Composition / Information on Ingredients

Ingredient Name		CAS Number		%			
Bisphenol A Epoxy Resin		25068-38-6		10 - 30			
Tri(dimethylaminomethyl)phenol		90-72-2		1 - 5			
Ingredient	OSHA PEL TWA	OSHA PEL STEL	ACGIH TLV TWA	ACGIH TLV STEL	NIOSH REL TWA	NIOSH REL STEL	NIOSH IDLH
Bisphenol A Epoxy resin	None estab.	None estab.	None estab.	None estab.	None estab.	None estab.	None estab.
Tri(dimethylaminomethyl)phenol	None estab.	none estab.	None estab.	none estab.	None estab.	None estab.	None estab.

Section 3 - Hazards Identification

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

HMIS

H 1

F 1

R 0

PPE†B

†Sec. 8

Potential Health Effects

Acute Effects

Inhalation: None.

Eye: Possible irritant and sensitizer.

Skin: Possible irritant and sensitizer.

Ingestion: Irritation of intestinal tract.

Chronic Effects: Warning! Respirable crystalline silica (quartz) is classified as a probable carcinogen. The crystalline silica present in this product is encapsulated in the epoxy resin and could only be liberated by sanding or abrading, and then not as pure crystalline silica. Appropriate precautions, however, should be taken, if the product is sanded or abraded to preclude personnel from breathing the dust.

Section 4 - First Aid Measures

Inhalation: Remove to fresh air.

Eye Contact: Flush with water, consult a physician.

Skin Contact: Wash with soap and water.

Ingestion: Seek medical advice

Section 5 - Fire-Fighting Measures


Flash Point: N/A.

Flammability Classification: IIIB

Extinguishing Media: Water spray, foam, CO2, dry chemicals.

Hazardous Combustion Products: CO, Aldehydes, acids, oxides of sulfur and nitrogen may be formed.

NFPA



Fire-Fighting: Fire fighters and others who may be exposed to the products of combustion should be equipped with NIOSH-approved positive pressure self contained breathing apparatus (SCBA) and full protective clothing.

Section 6 - Accidental Release Measures

Spill /Leak Procedures: Dispose of in normal manner.

Disposal: Incinerate in furnace or bury in landfill according to applicable regulations; not a hazardous waste.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Section 7 - Handling and Storage

Ventilation: Provide general or local exhaust ventilation systems if product is sanded or ground.

Respiratory Protection: Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator.

Protective Clothing/Equipment: Wear chemically protective gloves to prevent skin contact. Wear protective eyeglasses or chemical safety goggles.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Handling Precautions: None

Storage Requirements: Storage temperature: <90°F(32°C). Store in a cool, dry, well ventilated area.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Section 8 - Exposure Controls / Personal Protection

Ventilation: Provide general or local exhaust ventilation systems if product is sanded or ground.

Respiratory Protection: Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator.

Protective Clothing/Equipment: Wear chemically protective gloves to prevent skin contact. Wear protective eyeglasses or chemical safety goggles.

Section 9 - Physical and Chemical Properties

Form: Putty.

Appearance: Gray stick.

Odor: Mercaptan.

Solubility (in water): insoluble in water.

% Volatile: < 1%

Specific Gravity (H₂O=1, at 4 °C): 1.92

VOC: <1%

pH: >8

Section 10 - Stability and Reactivity

Stability: PC PLUMBING EPOXY PUTTY is stable.

Polymerization: Hazardous polymerization cannot occur.

Section 11- Toxicological Information

Toxicity Data:*

Lethal Dose Information(mg/kg)		Oral	Skin	Inhale	LC50
Bisphenol A Epoxy Resin		11400.00 rat	20000 rabbit	No data	No data
Tri(dimethylaminomethyl)phenol		1635.00 rat	1350.00 rabbit estimated	No data	No data

Section 12 - Ecological Information

Ecotoxicity: No data

Environmental Fate: No data

Environmental Degradation: No data

Soil Absorption/Mobility: No data

Section 13 - Disposal Considerations

Disposal: Incinerate in furnace or bury in landfill according to applicable regulations; not a hazardous waste.

Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

Section 14 - Transport Information

DOT Transportation Data (49 CFR 172.101):

Shipping Name: Not regulated	Packing Group: Not determined
Shipping Symbols: Not applicable.	Label: Not required
Hazard Class: Not Hazardous	Special Provisions (172.102):
ID No.: Not applicable.	None

Section 15 - Regulatory Information

EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33)
 RCRA Hazardous Waste Classification (40 CFR 261.??): Not classified
 CERCLA Hazardous Substance (40 CFR 302.4) unlisted specific per RCRA, Sec. 3001; CWA, Sec. 311 (b)(4); CWA, Sec. 307(a), CAA, Sec. 112
 CERCLA Reportable Quantity (RQ), Not listed.
 SARA 311/312 Codes: None.
 SARA Toxic Chemical (40 CFR 372.65): Not listed.
 SARA EHS (Extremely Hazardous Substance) (40 CFR 355): Not listed.

OSHA Regulations:

Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A): Not listed
 OSHA Specifically Regulated Substance, none

State Regulations:

Right-to-know: The non-hazardous ingredients in this product subject to the Pennsylvania, New Jersey, and/or Massachusetts right-to-know laws are:

CAS	NAME
144807-96-6	Magnesium Silicate Hydrate
Trade Secret	Polyether Polymercaptan
65997-17-3	Soda Lime Borosilicate Glass

Section 16 - Other Information

Storage Requirements: Storage temperature: <90°F(32°C). Store in a cool, dry, well ventilated area.

Personal Hygiene: Wash thoroughly after handling, especially before eating, drinking, smoking, and using restroom facilities. Wash contaminated goggles, faceshield, and gloves.

Prepared By: Charles Moloney

Revision Notes:

Notes: A bulletin such as this cannot be expected to cover all possible individual situations. As the user has the responsibility to provide a safe workplace, all aspects of an individual operation should be examined to determine if, or where, precautions- in addition to those described herein- are required. Any health hazard and safety information herein should be passed on to your customers or employees as the case may be.

Disclaimer: The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by the use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Final determination of suitability of the chemical is the sole responsibility of the user. No representation or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any other natures are made hereunder with respect to the information refers. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.