



Safety Data Sheet

Issue Date: 14-Mar-2012

Revision Date: 07-Nov-2018

Version 2

1. IDENTIFICATION

Product identifier

Product Name PC Metal Epoxy Putty

Other means of identification

SDS # 130606-24R

Recommended use of the chemical and restrictions on use

Recommended Use Adhesives.

Details of the supplier of the safety data sheet

Supplier Address

Protective Coatings Co.
221 S Third St.
Allentown, PA 18102 USA

Emergency telephone number

Company Phone Number 610-432-3543 / 800-220-2103
Emergency Telephone INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Aluminum stick

Physical state Solid

Odor Mercaptan

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1

Signal Word

Warning

Hazard statements

Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction



Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
 Wear protective gloves/protective clothing/eye protection/face protection
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Contaminated work clothing must not be allowed out of the workplace

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN: Wash with plenty of water and soap
 Take off contaminated clothing and wash before reuse
 If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Toxic to aquatic life with long lasting effects

Unknown Acute Toxicity

NOTE: Acute Toxicity classifications / calculations are approximates

3. COMPOSITION/INFORMATION ON INGREDIENTS

Please also refer to subsequent sections of this SDS for additional information regarding the components of this product.

Chemical name	CAS No	Weight-%
Talc	14807-96-6	30-60
Glass Beads	65997-17-3	10-30
Bisphenol A - Epichlorohydrin polymer	25068-38-6	10-30
Crystalline silica	14808-60-7	0.1-1.0

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General Advice	Provide this SDS to medical personnel for treatment.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin Contact	Wash with soap and water. Remove and wash contaminated clothing before reuse. Get medical attention if irritation occurs.
Inhalation	Remove exposed individual(s) to fresh air for 20 minutes. Consult a physician/poison center if individual's condition declines or if symptoms persist.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Seek medical advice.

Most important symptoms and effects, both acute and delayed

Symptoms Causes eye irritation. Causes skin irritation. May cause an allergic skin reaction. Direct contact may cause temporary redness and discomfort.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Skin and eye conditions may be aggravated by long term exposure.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, CO2 or water spray.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Product is not flammable.

Hazardous combustion products Carbon monoxide, Carbon dioxide (CO2), Aldehydes,

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Wear positive pressure self-contained breathing apparatus (SCBA). Do not release runoff from fire control methods to sewers or waterways. NFPA Class IIIB.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Wear protective gloves/protective clothing and eye/face protection. Avoid breathing vapors, mist or gas. Remove any contaminated clothing and wash thoroughly before reuse.

For Emergency Responders Follow applicable OSHA regulations (29 CFR 1910.120).

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Dispose of contents/container to an approved waste disposal plant.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Wear appropriate personal protective equipment. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash face, hands and any exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Store contents under <90F (32C) . NFPA Class IIIB storage.
Incompatible Materials	None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Exposure Guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Talc 14807-96-6	TWA: 2 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	(vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more; use Quartz limit	IDLH: 1000 mg/m ³ TWA: 2 mg/m ³ containing no Asbestos and <1% Quartz respirable dust
Glass Beads 65997-17-3	TWA: 1 fiber/cm ³ respirable fibers: length >5 μm, aspect ratio >=3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination TWA: 5 mg/m ³ inhalable particulate matter	-	-
Crystalline silica 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 μg/m ³ TWA: 50 μg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

Other Information	If product is sanded, appropriate respirator should be worn to avoid breathing dust. Pre-existing respiratory disorders may be aggravated by exposure. If sanded, this material may generate silica dust. Inhaled silica has been classified by IARC as a human carcinogen (see section 11).
--------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Appropriate engineering controls

Engineering Controls	Provide general or local exhaust ventilation if product is sanded or ground.
-----------------------------	------------------------------------------------------------------------------

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Chemical safety goggles/faceshield. Refer to 29 CFR 1910.133 for eye and face protection regulations.
Skin and Body Protection	Chemical resistant protective gloves. Wear suitable protective clothing. Reference Wiley's "Quick Selection Guide to Chemical Protective Clothing". Refer to 29 CFR 1910.138 for appropriate skin and body protection.
Respiratory Protection	Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator.

General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.
---------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Solid	Odor	Mercaptan
Appearance	Aluminum stick	Odor Threshold	Not determined
Color	Not determined		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	>8	
Melting point / freezing point	Not determined	
Boiling point / boiling range	Not determined	
Flash point	Not available	
Evaporation Rate	Not determined	
Flammability (Solid, Gas)	Not determined	
Flammability Limit in Air		
Upper flammability or explosive limits	Not determined	
Lower flammability or explosive limits	Not determined	
Vapor Pressure	Not determined	
Vapor Density	Not determined	
Relative Density	2.18 @ 4°C (39.2°F)	
Water Solubility	Insoluble in water	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Autoignition temperature	Not determined	
Decomposition temperature	Not determined	
Kinematic viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

Other information

VOC Content (%) <1%

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Keep out of reach of children.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact	Causes serious eye irritation.
Skin Contact	May cause an allergic skin reaction. Causes skin irritation.
Inhalation	Under normal conditions of intended use, this material is not expected to be an inhalation hazard.
Ingestion	May cause discomfort if swallowed.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Bisphenol A - Epichlorohydrin polymer 25068-38-6	= 11400 mg/kg (Rat)	20000 mg/kg (rabbit)	-
Ferrosilicon 8049-17-0	-	> 20 g/kg (Rabbit)	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause an allergic skin reaction.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen. However, the product as a whole has not been tested. Crystalline Silica is considered to be a human carcinogen when in respirable form (dust / powder).

Chemical name	ACGIH	IARC	NTP	OSHA
Talc 14807-96-6		Group 3		X
Glass Beads 65997-17-3		Group 3		
Crystalline silica 14808-60-7	A2	Group 1	Known	X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

Unknown Acute Toxicity NOTE: Acute Toxicity classifications / calculations are approximates.

Oral LD50 38,000.00 mg/kg

Dermal LD50 66,733.30 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Talc 14807-96-6		100: 96 h Brachydanio rerio g/L LC50 semi-static	

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Not determined

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. TRANSPORT INFORMATION

Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

Not regulated

IATA

Not regulated

IMDG

Not regulated

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
Talc	X	X	X	X	X	X	X	X
Bisphenol A - Epichlorohydrin polymer	X	X	X	X	X	X	X	X
Glass Beads	X	X	X	X	X	X	X	X
Ferrosilicon		X					X	
Mercaptan terminated polymer	X	X			X	X	X	X
Nepheline Syenite		X			X			

Crystalline silica	X	X	X	X	X	X	X	X
--------------------	---	---	---	---	---	---	---	---

Legend:

- TSCA* - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL* - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS* - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS* - Japan Existing and New Chemical Substances
- IECSC* - China Inventory of Existing Chemical Substances
- KECL* - Korean Existing and Evaluated Chemical Substances
- PICCS* - Philippines Inventory of Chemicals and Chemical Substances
- AICS* - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

SARA 313

Not determined

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Crystalline silica - 14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Talc 14807-96-6	X	X	X
Ferrosilicon 8049-17-0	X		
Crystalline silica 14808-60-7	X	X	X

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	1	1	0	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical hazards	Personal Protection
	1	1	0	B- Safety Glasses, Gloves

Issue Date: 14-Mar-2012
 Revision Date: 07-Nov-2018
 Revision Note: Formula update

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet