Safety Data Sheet



Issue Date: 06-Sep-2011 Revision Date: 26-Feb-2020 Version 2

1. IDENTIFICATION

Product identifier

Product Name PC-7, Part A

Other means of identification

SDS # 130519-23C

Recommended use of the chemical and restrictions on use

Recommended Use

Multi-purpose epoxy paste.

Details of the supplier of the safety data sheet

Supplier Address

Protective Coatings Co. 221 S Third St.

Allentown, PA 18102 USA

Emergency telephone number

Company Phone Number 610-432-3543 / 800-220-2103

Emergency Telephone INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Grey paste Physical state Paste Odor Mild

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1

Signal Word Warning

Hazard statements

Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction



Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing must not be allowed out of the workplace

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of water and soap

Take off contaminated clothing and wash before reuse

If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Not applicable

Mixture

Please also refer to subsequent sections of this SDS for additional information regarding the components of this product.

Chemical name	CAS No	Weight-%
Bisphenol A - Epichlorohydrin polymer	25068-38-6	40-70
Talc	14807-96-6	20-40
Soda lime borosilicate glass	65997-17-3	1-5
Titanium dioxide	13463-67-7	1-5

^{**}If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.**

4. FIRST AID MEASURES

Description of first aid measures

General Advice Provide this SDS to medical personnel for treatment. After first aid, get appropriate in-plant,

paramedic, or community medical support.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. If eye irritation persists: Get medical

advice/attention.

Skin Contact Wash with soap and water. Remove and wash contaminated clothing before reuse. Discard

items which cannot be decontaminated, including leather articles such as shoes, belts and

watchbands. If skin irritation or rash occurs: Get medical advice/attention.

Inhalation Remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, give

artificial respiration. Get medical attention immediately.

Ingestion Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting.

Never give anything by mouth to an unconscious person. Seek medical advice.

Revision Date: 26-Feb-2020 130519-23C - PC-7, Part A

Self-Protection of the First Aider First Aid responders should pay attention to self-protection and use the recommended

protective clothing (chemical resistant gloves, splash protection). If potential for exposure

exists refer to Section 8 for specific personal protective equipment.

Most important symptoms and effects, both acute and delayed

Symptoms Causes eye irritation. Direct contact may cause temporary redness and discomfort. Causes

skin irritation. Inhalation only possible at elevated temperatures. May cause irritation. May

cause an allergic skin reaction.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Skin and eye conditions may be aggravated by long term exposure.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, CO2 or water spray.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Product is not flammable.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO2). Aldehydes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Wear positive pressure self-contained breathing apparatus (SCBA). Do not release runoff from fire control methods to sewers or waterways. NFPA Class IIIB.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Dispose of contents/container to an approved waste disposal plant.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Wear appropriate

> personal protective equipment. Do not eat, drink or smoke when using this product. Wash face, hands and any exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Avoid breathing dust/fume/gas/mist/vapors/spray.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store contents under

<90F (32C) . NFPA Class IIIB storage.

Incompatible MaterialsNone known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Talc	TWA: 2 mg/m³ particulate matter	(vacated) TWA: 2 mg/m ³	IDLH: 1000 mg/m ³
14807-96-6	containing no asbestos and <1%	respirable dust <1% Crystalline	TWA: 2 mg/m ³ containing no
	crystalline silica, respirable	silica, containing no Asbestos	Asbestos and <1% Quartz
	particulate matter	TWA: 20 mppcf if 1% Quartz or	respirable dust
		more;use Quartz limit	
Soda lime borosilicate glass	TWA: 1 fiber/cm3 respirable	-	-
65997-17-3	fibers: length >5 µm, aspect ratio		
	>=3:1, as determined by the		
	membrane filter method at 400-		
	450X magnification [4-mm		
	objective], using phase-contrast		
	illumination		
	TWA: 5 mg/m³ inhalable fraction		
Titanium dioxide	TWA: 10 mg/m ³	TWA: 15 mg/m³ total dust	IDLH: 5000 mg/m ³
13463-67-7		(vacated) TWA: 10 mg/m ³ total	TWA: 2.4 mg/m ³ CIB 63 fine
		dust	TWA: 0.3 mg/m ³ CIB 63 ultrafine,
			including engineered nanoscale

Other Information

If product is sanded, appropriate respirator should be worn to avoid breathing dust. Preexisting respiratory disorders may be aggravated by exposure. If sanded, this material may generate titanium dioxide dust. Inhaled titanium dioxide has been classified by IARC as a human carcinogen (see section 11).

Appropriate engineering controls

Engineering Controls

Provide general or local exhaust ventilation if product is sanded or ground. Maintain eye wash fountain and quick-drench facilities in work area.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Chemical safety goggles/faceshield. Refer to 29 CFR 1910.133 for eye and face protection

regulations.

Skin and Body Protection Wear protective gloves and protective clothing. Refer to 29 CFR 1910.138 for appropriate

skin and body protection.

Respiratory Protection Ensure adequate ventilation, especially in confined areas. If engineering controls do not

keep airborne concentrations below acceptable levels, wear a NIOSH-approved respirator.

Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Avoid contact with skin, eyes and clothing. After handling this product, wash hands before

eating, drinking, or smoking. If contact occurs, remove contaminated clothing. If needed, take first aid action shown on section 4 of this SDS. Launder contaminated clothing before

reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Paste

Appearance Grey paste Odor Mild

Color Grey Odor Threshold Not determined

Property Values Remarks • Method

 \overline{pH} >/=2.0 - </=12.0

Melting point / freezing point Not available Boiling point / boiling range No data

Flash point 248.88 °C / 480 °F CC (closed cup)

Evaporation Rate Not determined Flammability (Solid, Gas) Not determined

Flammability Limit in Air

Upper flammability or explosive Not available

limits

Lower flammability or explosive Not available

limits

Vapor PressureNot determinedVapor DensityNot available

Relative Density 1.15 @ 60°F (ASTM D 1298)

Water Solubility Insoluble in water

Solubility in other solvents Alcohols **Partition Coefficient** Not determined **Autoignition temperature** Not determined **Decomposition temperature** Not determined Not determined Kinematic viscosity **Dynamic Viscosity** Not determined **Explosive Properties** Not determined **Oxidizing Properties** Not determined

Other information

Liquid Density 9.5 lbs/gal

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Keep out of reach of children.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Causes serious eye irritation.

Skin Contact Causes skin irritation. May cause an allergic skin reaction.

Inhalation Under normal conditions of intended use, this material is not expected to be an inhalation

hazard.

Ingestion May cause discomfort if swallowed.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Bisphenol A - Epichlorohydrin	= 11400 mg/kg (Rat)	20000 mg/kg (rabbit)	-
polymer			
25068-38-6			
Formaldehyde, polymer with	>2000 mg/kg (rat)	-	-
1,3,dimethylbenzene			
26139-75-3			
Polyethylene	> 2000 mg/kg (Rat) = 8 g/kg (Rat	-	-
9002-88-4)		
Titanium dioxide	> 10000 mg/kg (Rat)	-	-
13463-67-7			

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause an allergic skin reaction.

Carcinogenicity Titanium dioxide is a possible carcinogen when it appears as a respirable dust.

Chemical name	ACGIH	IARC	NTP	OSHA
Talc		Group 3		X
14807-96-6				
Soda lime borosilicate glass		Group 3		
65997-17-3				
Polyethylene		Group 3		
9002-88-4				
Titanium dioxide		Group 2B		X
13463-67-7		·		

Legend

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document Values exceed classification criteria.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Talc		100: 96 h Brachydanio rerio g/L	
14807-96-6		LC50 semi-static	

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Not determined

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of WastesDisposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

DOT Not regulated

IATA Not regulated

IMDG Not regulated

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	TSCA Inventory	DSL/NDSL		ENCS	IECSC	KECL	PICCS	AICS
		Status		NCS					
Bisphenol A -	Χ	ACTIVE	X	X	Χ	X	X	X	X
Epichlorohydrin polymer									
Talc	Х	ACTIVE	X	X	Х	Х	Х	X	Х
Formaldehyde, polymer with	Х	ACTIVE	Х		Х	X	Х	X	X
1,3,dimethylbenzene									
Soda lime borosilicate glass	Χ	ACTIVE	Х	X	Χ	Χ	Х	X	Χ
Polyethylene	Х	ACTIVE	Х		Χ	Χ	Х	X	Χ
Titanium dioxide	Х	ACTIVE	X	X	Х	Х	Х	X	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

SARA 313

Not determined

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Talc	X	X	X
14807-96-6			
Titanium dioxide 13463-67-7	X	X	X

16. OTHER INFORMATION

NFPA	Health Hazards	Flammability	Instability	Special Hazards
	2	1	0	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical hazards	Personal Protection
	2	1	0	B- Safety Glasses,
				Gloves

Issue Date:06-Sep-2011Revision Date:26-Feb-2020Revision Note:Regulatory review

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet





Issue Date: 06-Sep-2011 Revision Date: 26-Feb-2020 Version 2

1. IDENTIFICATION

Product identifier

Product Name PC-7, Part B

Other means of identification

SDS # 130519-20C

Recommended use of the chemical and restrictions on use

Recommended Use

Multi-purpose epoxy paste.

Details of the supplier of the safety data sheet

Supplier Address

Protective Coatings Co. 221 S Third St.

Allentown, PA 18102 USA

Emergency telephone number

Company Phone Number 610-432-3543 / 800-220-2103

Emergency Telephone INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

AppearanceBlack pastePhysical statePasteOdorSlight amine

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1

Signal Word Warning

Hazard statements

Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction



Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing must not be allowed out of the workplace

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of water and soap Take off contaminated clothing and wash before reuse

If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Please also refer to subsequent sections of this SDS for additional information regarding the components of this product.

Chemical name	CAS No	Weight-%
Talc	14807-96-6	10-30
Kaolin	1332-58-7	15-30
Triethylene tetramine	112-24-3	1-5
Soda lime borosilicate glass	65997-17-3	1-5
Ceramic Fiber	142844-00-6	1-5
Carbon Black	1333-86-4	<1

^{**}If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.**

4. FIRST AID MEASURES

Description of first aid measures

General Advice Provide this SDS to medical personnel for treatment. After first aid, get appropriate in-plant,

paramedic, or community medical support.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. If eye irritation persists: Get medical

advice/attention.

Skin Contact Wash with soap and water. Remove and wash contaminated clothing before reuse. If skin

irritation or rash occurs: Get medical advice/attention.

Inhalation Remove exposed individual(s) to fresh air for 20 minutes. Consult a physician/poison center

if individual's condition declines or if symptoms persist.

Ingestion Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting.

Never give anything by mouth to an unconscious person. Get medical attention if you feel

unwell.

Most important symptoms and effects, both acute and delayed

Symptoms Causes eye and skin irritation. May cause an allergic skin reaction. May be harmful if

swallowed. Direct contact may cause temporary redness and discomfort. May cause

discomfort if swallowed. May be harmful in contact with skin.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Skin and eye conditions may be aggravated by long term exposure.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, CO2 or water spray.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Product is not flammable.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO2). Aldehydes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Wear positive pressure self-contained breathing apparatus (SCBA). Do not release runoff from fire control methods to sewers or waterways. NFPA Class IIIB.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Wear protective gloves/protective clothing and eye/face protection. Remove any

contaminated clothing and wash thoroughly before reuse.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Dispose of contents/container to an approved waste disposal plant.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Wear appropriate

personal protective equipment. Do not eat, drink or smoke when using this product. Wash face, hands and any exposed skin thoroughly after handling. Avoid breathing

lace, harlus and any exposed skin thoroughly after harluing. Avoid breathing

dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store contents under

<90F (32C) . NFPA Class IIIB storage.

Incompatible Materials The symbol (*) in the margin of this SDS indicates that this line has been revised.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Talc	TWA: 2 mg/m³ particulate matter		IDLH: 1000 mg/m ³
14807-96-6	containing no asbestos and <1%		TWA: 2 mg/m³ containing no
	crystalline silica, respirable	silica, containing no Asbestos	Asbestos and <1% Quartz
	particulate matter	TWA: 20 mppcf if 1% Quartz or	respirable dust
		more;use Quartz limit	
Kaolin	TWA: 2 mg/m³ particulate matter		TWA: 10 mg/m ³ total dust
1332-58-7	containing no asbestos and <1%	TWA: 5 mg/m ³ respirable	TWA: 5 mg/m ³ respirable dust
	crystalline silica, respirable	fraction	
	particulate matter	(vacated) TWA: 10 mg/m ³ total	
		dust	
		(vacated) TWA: 5 mg/m ³	
		respirable fraction	
Soda lime borosilicate glass	TWA: 1 fiber/cm3 respirable	-	-
65997-17-3	fibers: length >5 μm, aspect ratio		
	>=3:1, as determined by the		
	membrane filter method at		
	400-450X magnification [4-mm		
	objective], using phase-contrast		
	illumination		
	TWA: 5 mg/m³ inhalable fraction		
Ceramic Fiber	TWA: 0.2 fiber/cm3 respirable	-	-
142844-00-6	fibers: length >5 μm, aspect ratio		
	>=3:1, as determined by the		
	membrane filter method at		
	400-450X magnification [4-mm		
	objective], using phase-contrast		
	illumination	-	
Carbon Black	TWA: 3 mg/m ³ inhalable	TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³
1333-86-4	particulate matter	(vacated) TWA: 3.5 mg/m ³	TWA: 3.5 mg/m ³
			TWA: 0.1 mg/m³ Carbon black in
			presence of Polycyclic aromatic
			hydrocarbons PAH

Pre-existing respiratory disorders may be aggravated by exposure. If sanded, this material may generate Ceramic fiber dust. Inhaled fibers have been classified by IARC as a human

carcinogen (see section 11).

Appropriate engineering controls

Engineering Controls Provide general or local exhaust ventilation if product is sanded or ground. Maintain eye

wash fountain and quick-drench facilities in work area.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Chemical safety goggles/faceshield. Refer to 29 CFR 1910.133 for eye and face protection

regulations.

Skin and Body Protection Wear protective gloves and protective clothing. Refer to 29 CFR 1910.138 for appropriate

skin and body protection.

Respiratory Protection Ensure adequate ventilation, especially in confined areas. If engineering controls do not

keep airborne concentrations below acceptable levels, wear a NIOSH-approved respirator.

Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes and clothing. After handling this product, wash hands before eating, drinking, or smoking. If contact occurs, remove contaminated clothing. If needed, take first aid action shown on section 4 of this SDS. Launder contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical statePasteAppearanceBlack pasteOdorSlight amineColorBlackOdor ThresholdNot determined

Property Values Remarks • Method

pH >/= 2.0 - </= 12.0

Melting point / freezing point Not available

Boiling point / boiling range No data

Flash point 110 °C / 230 °F CC (closed cup)

Evaporation Rate Not determined Flammability (Solid, Gas) Not determined

Flammability Limit in Air

Upper flammability or explosive Not available

limits

Lower flammability or explosive Not available

limits

Vapor PressureNot determinedVapor DensityNot available

Relative Density 0.86 @ 60°F (ASTM D 1298)

Water Solubility Insoluble in water

Solubility in other solvents Alcohols **Partition Coefficient** Not determined **Autoignition temperature** Not determined **Decomposition temperature** Not determined Kinematic viscosity Not determined **Dynamic Viscosity** Not determined **Explosive Properties** Not determined **Oxidizing Properties** Not determined

Other information

Liquid Density 7.2 lbs/gal

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Excessive heat over long periods of time.

Incompatible materials

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Hazardous decomposition products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Causes eye irritation.

Skin Contact Causes skin irritation. May cause an allergic skin reaction. May be harmful in contact with

skin.

Inhalation Under normal conditions of intended use, this material is not expected to be an inhalation

hazard.

Ingestion May cause discomfort if swallowed. May be harmful if swallowed.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Aliphatic Polyaminoamide 68410-23-1	>2000 mg/kg (rat)	2000 mg/kg (rat)	-
Kaolin 1332-58-7	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rat)	-
Triethylene tetramine 112-24-3	= 2500 mg/kg (Rat)	= 550 mg/kg (Rabbit)	-
Formaldehyde, polymer with 1,3,dimethylbenzene 26139-75-3	>2000 mg/kg (rat)	-	-
Polyethylene 9002-88-4	> 2000 mg/kg (Rat) = 8 g/kg (Rat)	-	-
Carbon Black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause an allergic skin reaction.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

However, the product as a whole has not been tested. Carbon black is a possible

carcinogen when it appears as a respirable dust. Ceramic Fiber is a possible carcinogen

when it appears as a respirable dust.

Chemical name	ACGIH	IARC	NTP	OSHA
Talc		Group 3		X
14807-96-6				
Ceramic Fiber	A2	Group 2B	Reasonably Anticipated	X
142844-00-6		•		

Soda lime borosilicate glass 65997-17-3		Group 3	
Polyethylene 9002-88-4		Group 3	
Carbon Black 1333-86-4	A3	Group 2B	Х

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen
IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans
Group 3 IARC components are "not classifiable as human carcinogens"
NTP (National Toxicology Program)
Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document ...

Oral LD50 3,395.00 mg/kg **Dermal LD50** 2,380.00 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Component Information

ſ	Chemical name	Algae/aquatic plants	Fish	Crustacea
Ī	Talc		100: 96 h Brachydanio rerio g/L	
	14807-96-6		LC50 semi-static	
	Triethylene tetramine 112-24-3	20: 72 h Pseudokirchneriella subcapitata mg/L EC50 3.7: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.5: 72 h Desmodesmus subspicatus mg/L EC50	495: 96 h Pimephales promelas mg/L LC50 570: 96 h Poecilia reticulata mg/L LC50 semi-static	31.1: 48 h Daphnia magna mg/L EC50
	Carbon Black 1333-86-4			5600: 24 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Chemical name	Partition coefficient
Triethylene tetramine	-1.4
112-24-3	

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

DOT Not regulated

IATA Not regulated

<u>IMDG</u> Not regulated

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	TSCA Inventory Status	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
Aliphatic Polyaminoamide	Х	ACTIVE	Х		Х	Х	Х	Х	Х
Talc	Х	ACTIVE	Х	X	Х	Х	Х	X	Х
Kaolin	Х	ACTIVE	Х	Х		Х	Х	Х	Х
prop-1-en-2-ylbenzene; styrene	Х	ACTIVE	Х			Х	Х	Х	Х
Triethylene tetramine	Х	ACTIVE	Х	X	Х	Х	Х	Х	Х
Ceramic Fiber						X			
Formaldehyde, polymer with 1,3,dimethylbenzene	Х	ACTIVE	Х		Х	Х	Х	Х	Х
Soda lime borosilicate glass	Х	ACTIVE	Х	X	Х	Х	Х	X	X
Polyethylene	Х	ACTIVE	Х		Χ	Х	Х	X	Х
Carbon Black	Х	ACTIVE	Х	X	Х	Х	Х	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

 $\textbf{\textit{DSL/NDSL}} \quad \text{-} \ \textit{Canadian Domestic Substances List/Non-Domestic Substances List}$

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

SARA 313

Not determined

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Ceramic Fiber - 142844-00-6	Carcinogen
Carbon Black - 1333-86-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Talc	X	X	X
14807-96-6			
Kaolin	X	X	X
1332-58-7			
Triethylene tetramine	X	X	X
112-24-3			
Ceramic Fiber	X		
142844-00-6			
Carbon Black	X	X	X
1333-86-4			

16. OTHER INFORMATION

NFPA_	Health Hazards	Flammability	Instability	Special Hazards
	2	1	0	Not determined
HMIS_	Health Hazards	Flammability	Physical hazards	Personal Protection
	2	1	0	B- Safety Glasses,
				Gloves

Issue Date:06-Sep-2011Revision Date:26-Feb-2020Revision Note:Regulatory update

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet